

PI TAPE® PRECISION DIAMETER TAPES

Authentic source for PI TAPE® products -Quality Products Since 1944-

Accuracy .001" (.03mm)	1095 Spring Steel (black numbers on silver)	716 Stainless Steel (black numbers on silver)	Blue Easy to Read Style (white numbers on blue)	White Easy to Read Style (dark numbers on white)
Diameter Range	Part#	Part#	Part#	Part#
.500" - 2" O.D.*	P000	P000SS	not avail.	P000WSS
.75" - 7" O.D.*	P01	P01SS	P01EZ	P01WSS
.75" - 9" O.D.*	P02	P02SS	P02EZ	P02WSS
2" - 12" O.D.	P1	P1SS	P1EZ	P1WEZ
2" - 24" O.D.	P1SP	P1SPSS	P1SPEZ	P1SPWEZ
12" - 24" O.D.	P2	P2SS	P2EZ	P2WEZ
12" - 36" O.D.	P2SP	P2SPSS	P2SPEZ	P2SPWEZ
24" - 36" O.D.	P3	P3SS	P3EZ	P3WEZ
24" - 48" O.D.	P3SP	P3SPSS	P3SPEZ	P3SPWEZ
36" - 48" O.D.	P4	P4SS	P4EZ	P4WEZ
48" - 60" O.D.	P5	P5SS	P5EZ	P5WEZ
60" - 72" O.D.	P6	P6SS	P6EZ	P6WEZ
72" - 84" O.D.	P7	P7SS	P7EZ	P7WEZ
84" - 96" O.D.	P8	P8SS	P8EZ	P8WEZ
96" - 108" O.D.	P9	P9SS	P9EZ	P9WEZ
108" - 120" O.D.	P10	P10SS	P10EZ	P10WEZ
120" - 132" O.D.	P11	P11SS	P11EZ	P11WEZ
132" - 144" O.D.	P12	P12SS	P12EZ	P12WEZ
15 - 50mm O.D.*	PM000	PM000SS	not avail.	PM000WSS
28 - 200mm O.D.*	PM0	PM0SS	PM0EZ	PM0WSS
28 - 300mm O.D.*	PM02	PM02SS	PM02EZ	PM02WSS
50 - 300mm O.D.	PM03	PM03SS	PM03EZ	PM03WEZ
100 - 300mm O.D.	PM1	PM1SS	PM1EZ	PM1WEZ
50 - 600mm O.D.	PM1SP	PM1SPSS	PM1SPEZ	PM1SPWEZ
300 - 600mm O.D.	PM2	PM2SS	PM2EZ	PM2WEZ
300 - 900mm O.D.	PM2SP	PM2SPSS	PM2SPEZ	PM2SPWEZ
600 - 900mm O.D.	PM3	PM3SS	PM3EZ	PM3WEZ
600 - 1200mm O.D.	PM3SP	PM3SPSS	PM3SPEZ	PM3SPWEZ
900 - 1200mm O.D.	PM4	PM4SS	PM4EZ	PM4WEZ
1200 - 1500mm O.D.	PM5	PM5SS	PM5EZ	PM5WEZ
1500 - 1800mm O.D.	PM6	PM6SS	PM6EZ	PM6WEZ
1800 - 2100mm O.D.	PM7	PM7SS	PM7EZ	PM7WEZ
2100 - 2400mm O.D.	PM8	PM8SS	PM8EZ	PM8WEZ
2400 - 2700mm O.D.	PM9	PM9SS	PM9EZ	PM9WEZ
2700 - 3000mm O.D.	PM10	PM10SS	PM10EZ	PM10WEZ
3000 - 3300mm O.D.	PM11	PM11SS	PM11EZ	PM11WEZ
3300 - 3600mm O.D.	PM12	PM12SS	PM12EZ	PM12WEZ

Standard tapes are manufactured with a 1/4" wide Vernier Gage, a 1/2" wide Main Body and a 1/4" wide Gage Member The standard thickness is .010" (0.25mm) for tapes with a starting point of 2" (50mm) or larger *Smaller sizes have a thickness of either .006" (0.15mm) or .007" (0.18mm) depending on the material type Calibration Report traceable to N.I.S.T. is furnished with each new tape at no additional charge Our calibration lab is compliant with ANSI/NCSL Z540-1-1994, ISO 17025, ISO 10012-1, MIL-STD 45662A and 10CFR21 Larger diameters, special sizes, special widths and Go/No-Go tapes can be manufactured to suit your requirements I.D. tapes are available in most sizes Please specify Inside Diameter when ordering



ATRYA PLAST

MÉXICO Ciudad de Mexico Tel +52 (55) 2603 7450 ventas@atrya.com.mx www.atrya.com.mx

© Copyright 2003-2017 Pi Tape Texas, LLC. - All rights reserved Made in the USA



Our manufacturing plant is now located in Tyler, Texas

All offers, price quotes, negotiations, acceptances, agreements, obligations, deliveries, invoices, and performance relating thereto shall be deemed for all purposes to have been fully offered, provided, negotiated, accepted, executed, delivered, incurred, and performed within the State of Texas, and no contract or obligations shall be deemed to arise unless and until the same are accepted by Pi Tape Texas in the State of Texas. The rights and obligations of the parties hereunder, and any action arising from or relating to this agreement or the subject matter hereof, shall be construed and enforced in accordance with, and governed by, the laws of the State of Texas.