


Charting data:



The value of charting or graphing data makes finding trends and seeing quality and process issues much quicker and easier.



Grouping data charts:

Tracking similar properties can be easy to set-up with the grouping tool. It is a simple process to set these up per grade, paper machine or for customer trials.



Overlaying data charts:

Certain properties trend together and can create a powerful visual and analysis tool. PROFILE/Plus® Controller gives you the capabilities to set these overlays of properties to best optimize your operations.

Additional software features in the PROFILE/Plus® Controller:

- Historical data review and analysis
- New and improved operator interface
- Simplified system configurations and updates
- FTP mill interface
- Measurement and data zoning



PROFILE/Plus® Controller Specifications:

PPC Hardware Specification

I/O Ports	• 1x HDMI External display • 4x USB Type A • 1x RJ45 Mill Connection • USB Printer support for 90% of 2012 and newer printers
------------------	---

Instrument Interface Ports


Number of Serial Ports	8 or 16 via RS232 DTE on RJ45 (10 pin)
Serial Port Speed	300bps to 230kbps
Data Bits	8-bit protocol support
Parity	Odd, Even, Mark, Space, None
Flow Control	Hardware, Software, Both, None
Serial Port Protection	15Kv Electrostatic Discharge Protection (ESD)
Total Weight	57lbs/26kg

Mill Connection Port

Data Port (1)	10/100/1000 RJ45 Port
Security	ACL-Based Firewall State-Based Firewall NAT
Ethernet Isolation	1.5Kv Magnetic Isolation
Mill Connection	IP4 Manual or DHCP Client
Data Protocol	FTP Data Export

Display Specification

Digital Size	15.6" diagonal, Active matrix TFT LCD (LED)
Aspect Ratio	16:9
Touch Interface	USB
Speakers (2)	2W Internal Speaker
Monitor Dimensions (With Stand)	11.21" x 15.23" x 7.84" 28.5cm x 38.7cm x 19.9cm
Weight (Unpacked)	6.72lbs/3.05kg



Contact Details

web. www.industrialphysics.com
email. info@industrialphysics.com
email. info.china@industrialphysics.com