

Practum ®

**Laboratory Balances** 

Simplifying Progress

SARTURIUS



ATRYA PLAST S.A. DE C.V.



# Start Weighing Right



Get best value for your money, without compromises in precision and reliability. Rely on consistent readings and excellent repeatability ensured by Sartorius quality and technology developed and designed in Germany.







What I Like ....





Practical and Sturdy Draft Shield
The sturdy draft shield will stand up to the
daily use even by inexperienced operators.
Moreover, it can be completely disassembled
to conveniently clean the glass parts in
a dishwasher.

Supervisor Lock
This practical feature enables teachers and professors to lock the menu. As a result, students will concentrate on learning.

Rugged Weigh Cell for Reliable Results – Every Time, All the Time High-resolution, overload protected weigh cells, made in Germany, ensure durable and reliable performance of the Practum \*.

Changes Readily Documented by Interval-Controlled Printout of Weights The Practum \* will document weights automatically and reliably, such as slow filling processes.

Hassle-Free Below-Balance Weighing of Oversize Containers Extra-large volumes or magnetic substances are easy to weigh accurately using the easily accessible weighing port.

Extra-large Feet and Up-front Level
Indicator for Easy Leveling
Two large, easy-to-adjust feet and an outstandingly simple-to-read level indicator on the front make it a breeze for you to level the Practum \*. This helps ensure accurate, repeatable weighing results.

USB Port and Data Transfer to
Microsoft \* Excel for Perfect Records
The USB port automatically detects when a
Sartorius laboratory printer is connected to the
Practum \*. This interface also enables you to
transfer your weighing data directly into a
Microsoft \* Excel spreadsheet, without the
need for additional software.



## Start Weighing Right



You can't go wrong with the new Practum \*: a foolproof, exceptionally rugged and reliable lab balance.

Practum \* has everything you need for standard applications. So you pay only for what you really need.



#### Weighing

You name it, Practum \* will weigh it – from the smallest samples to the heaviest objects in the analytical range, and from entire chunks of solids to the finest quantities of pastes, powders and liquids, Practum \* provides incomparable weighing reliability.



#### **Peak Hold Function**

Forget now you see it, now you don't. Effortlessly read off the maximum force released in milliseconds when a switch is activated, or weigh a bulky sample that covers the display. Practum \* will conveniently determine and "hold" the peak value for you.



#### Percentage Weighing

If you need to compare different samples and determine how much they vary from a reference standard, this function will do the math for you.



#### **Animal Weighing**

Does your environment "rock" in the neg ative sense? Is it exposed to vibration or laminar flow? Or do you need to now the exact weight of a hyper little mouse that just won't sit still? Relax with "rocksteady" readings on Practum.



#### Checkweighing

Practum \* is ideal when you need to check whether different objects, such as packaged units, are within a specific tolerance range.



#### Counting

Use Practum \* to count identical materials, such as tablets, screws and similar parts. Using Practum \* is easier, faster and more accurate than manual counting.



#### **Density Determination**

With Practum \* and our Optional Density kit, you can easily and accurately deter mine the density of a solid object.

















### Practum \* – Technical Specifications

Model		224	124	64	513	313	213	3102	2102	1102	612	412	6101	5101	2101	6100	5100
Weighing capacity	g	220	120	60	510	310	210	3100	2100	1100	610	410	6100	5100	2100	6100	5100
Readability	mg	0.1	0.1	0.1	1	1	1	10	10	10	10	10	100	100	100	1000	1000
Repeatability	mg	0.1	0.1	0.1	1	1	1	10	10	10	10	10	100	100	100	500	500
Typical stabilization time	S	2	2	2	1	1	1	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1	1
Weighing pan size	Ø mm	90	90	90	120	120	120	180	180	180	180	180	180	180	180	180	180
Weighing chamber height	mm	209	209	209	209	209	209										
Dimensions D ×W ×H	mm	360 ×216×320 360 ×216×95															
	inch	14.1×8.5 ×12.6 14.1×8.5 ×3.75															
Data interface	Mini USB  – Automatic recognition of Sartorius printer models YDP40 and YDP20-0CE  – Direct data transfer to Microsoft * application programs without any additional software  – Programmable interval for data output  – Choice of SBI, table format or text format data transfer protocols																
Supervisor lock		Menu lock to prevent unintended manipulation															
Housing and draft shield		Robust and easy to clean housing with easy to operate draft shield (where applicable)															
Standard application programs		Weighing, Density, Percentage, Checkweighing, Peakhold, Counting and Animal weighing															
Theft lock		Kensington lock and lockdown capability for cable or chain															
In-use cover		Stanc	lard for a	all mode	ls												
Underfloor weighing		Integ	rated														
Technology and construction		Made	in Germ	nany													





Specifications subject to change without notice. Copyright Sartorius Lab Instruments GmbH & Co. KG. Status: 02 | 2022

MEXICO Tel. +52 (55) 2603 7450 NUEVO LEON Tel. +52 (81) 2235 9264 JALISCO Tel. +52 (33) 1543 3419